

Tri-ROW Roller Slewing Ring (Series 13) 130. No Gear

| No. | Type | | | Configuration & Structural Dimension | | | | | | | | | | Mounting Hole Dimension | | | | | | Gear Parameter | | | | | | Weight | | | |
|-----|---------------------------------|----------------------------|----------------------------|--------------------------------------|-------------|------------|------------|-----------|----------------|-------------|-------------|-------------|----|-------------------------|-------------|-----------|------------|-----------|------------|----------------|------------------------|------------|------------------|------------|------------------|-------------|--------------|--------------|------------|
| | 130 | 131 132 | 133 134 | D | d | H | H1 | h | 130 133/134 | | 131 132 | | n1 | D1 | D2 | n | Type 0 | | Type 1,2,3 | | b | m | 131 132 | | 133 134 | | 130 | 131 132 | 133 134 |
| | Steel Ball Spec. DL | | | | | | | | D3 | d1 | D3 | d1 | | | | | Φ | M | T | z | | | da | z | da | kg | | | |
| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 130.25.500 (25.500) | 131.25.500 132.25.500 | 133.25.500 134.25.500 | 634 | 366 | 148 | 138 | 32 | 474 | 463 | 537 | 526 | 4 | 598 | 402 | 24 | Φ18 | 16 | 32 | 80 | 5 6 | 130 108 | 664 664.8 | 68 57 | 337 338.4 | 191 | 200 200 | 198 198 | |
| 2 | 130.25.560 (25.560) | 131.25.560 132.25.560 | 133.25.560 134.25.560 | 694 | 426 | 148 | 138 | 32 | 534 | 523 | 597 | 586 | 4 | 658 | 462 | 25 | Φ18 | 16 | 32 | 80 | 5 6 | 142 118 | 724 724.8 | 80 67 | 397 398.4 | 214 | 224 224 | 222 220 | |
| 3 | 130.25.630 (25.630) | 131.25.630 132.25.630 | 133.25.630 134.25.630 | 764 | 496 | 148 | 138 | 32 | 604 | 593 | 667 | 656 | 4 | 728 | 532 | 28 | Φ18 | 16 | 32 | 80 | 6 8 | 132 98 | 808.8 806.4 | 77 58 | 458.4 459.2 | 240 | 262 257 | 253 251 | |
| 4 | 130.25.710 (25.710) | 131.25.710 132.25.710 | 133.25.710 134.25.710 | 844 | 576 | 148 | 138 | 32 | 684 | 673 | 747 | 736 | 4 | 808 | 612 | 28 | Φ18 | 16 | 32 | 80 | 6 8 | 145 108 | 886.8 886.4 | 90 68 | 536.4 539.2 | 272 | 295 291 | 288 284 | |
| 5 | 130.32.800 (32.800) | 131.32.800 132.32.800 | 133.32.800 134.32.800 | 964 | 636 | 182 | 172 | 40 | 770 | 759 | 841 | 830 | 4 | 920 | 680 | 36 | Φ22 | 20 | 40 | 120 | 8 10 | 123 98 | 1006.4 1008 | 75 60 | 595.2 594 | 459 | 490 487 | 483 481 | |
| 6 | 130.32.900 (32.900) | 131.32.900 132.32.900 | 133.32.900 134.32.900 | 1064 | 736 | 182 | 172 | 40 | 870 | 859 | 941 | 930 | 4 | 1020 | 780 | 36 | Φ22 | 20 | 40 | 120 | 8 10 | 135 108 | 1102.4 1108 | 87 70 | 691.2 694 | 519 | 549 562 | 551 545 | |
| 7 | 130.32.1000 (32.1000) | 131.32.1000 132.32.1000 | 133.32.1000 134.32.1000 | 1164 | 836 | 182 | 172 | 40 | 970 | 959 | 1041 | 1030 | 5 | 1120 | 880 | 40 | Φ22 | 20 | 40 | 120 | 10 12 | 119 99 | 1218 1221.6 | 79 66 | 784 784.8 | 577 | 631 631 | 618 613 | |
| 8 | 130.32.1120 (32.1120) | 131.32.1120 132.32.1120 | 133.32.1120 134.32.1120 | 1284 | 956 | 182 | 172 | 40 | 1090 | 1079 | 1161 | 1150 | 5 | 1240 | 1000 | 40 | Φ22 | 20 | 40 | 120 | 10 12 | 131 109 | 1338 1341.6 | 91 76 | 904 904.8 | 650 | 710 710 | 698 691 | |
| 9 | 130.40.1250 (40.1250) | 131.40.1250 132.40.1250 | 133.40.1250 134.40.1250 | 1445 | 1055 | 220 | 210 | 50 | 1213 | 1200 | 1300 | 1287 | 5 | 1393 | 1107 | 45 | Φ26 | 24 | 48 | 150 | 12 14 | 123 105 | 1509.6 1509.2 | 83 71 | 988.8 985.6 | 1038 | 1137 1126 | 1123 1122 | |
| 10 | 130.40.1400 (40.1400) | 131.40.1400 132.40.1400 | 133.40.1400 134.40.1400 | 1595 | 1205 | 220 | 210 | 50 | 1363 | 1350 | 1450 | 1437 | 5 | 1543 | 1257 | 45 | Φ26 | 24 | 48 | 150 | 12 14 | 136 116 | 1665.6 1663.2 | 96 82 | 1144.8 1139.6 | 1170 | 1299 1281 | 1254 1258 | |
| 11 | 130.40.1600 (40.1600) | 131.40.1600 132.40.1600 | 133.40.1600 134.40.1600 | 1795 | 1405 | 220 | 210 | 50 | 1563 | 1550 | 1650 | 1637 | 6 | 1743 | 1457 | 48 | Φ26 | 24 | 48 | 150 | 14 16 | 131 114 | 1873.2 1868.8 | 96 84 | 1335.6 1334.4 | 1341 | 1501 1471 | 1454 1448 | |
| 12 | 130.40.1800 (40.1800) | 131.40.1800 132.40.1800 | 133.40.1800 134.40.1800 | 1995 | 1605 | 220 | 210 | 50 | 1763 | 1750 | 1850 | 1837 | 6 | 1943 | 1657 | 48 | Φ26 | 24 | 48 | 150 | 14 16 | 145 127 | 2069.2 2076.8 | 110 96 | 1531.6 1526.4 | 1518 | 1682 1697 | 1658 1663 | |
| 13 | 130.45.2000 (45.2000) | 131.45.2000 132.45.2000 | 133.45.2000 134.45.2000 | 2221 | 1779 | 231 | 219 | 54 | 1967 | 1945 | 2055 | 2033 | 6 | 2155 | 1845 | 60 | Φ33 | 33 | 60 | 160 | 16 18 | 141 125 | 2300.8 2300.4 | 107 95 | 1702.4 1699.2 | 1494 | 2147 2129 | 2114 2112 | |
| 14 | 130.45.2240 (45.2240) | 131.45.2240 132.45.2240 | 133.45.2240 134.45.2240 | 2461 | 2019 | 231 | 219 | 54 | 2207 | 2185 | 2295 | 2273 | 6 | 2395 | 2085 | 60 | Φ33 | 33 | 60 | 160 | 16 18 | 157 139 | 2556.8 2552.4 | 121 108 | 1926.4 1933.2 | 2197 | 2501 2461 | 2447 2407 | |
| 15 | 130.45.2500 (45.2500) | 131.45.2500 132.45.2500 | 133.45.2500 134.45.2500 | 2721 | 2279 | 231 | 219 | 54 | 2467 | 2445 | 2555 | 2533 | 8 | 2655 | 2345 | 72 | Φ33 | 33 | 60 | 160 | 18 20 | 154 138 | 2822.4 2816 | 122 110 | 2185.2 2188 | 2590 | 2786 2731 | 2862 2834 | |
| 16 | 130.45.2800 (45.2800) | 131.45.2800 132.45.2800 | 133.45.2800 134.45.2800 | 3021 | 2579 | 231 | 219 | 54 | 2767 | 2745 | 2855 | 2833 | 8 | 2955 | 2645 | 72 | Φ33 | 33 | 60 | 160 | 18 20 | 170 153 | 3110.4 3116 | 139 125 | 2491.2 2488 | 2932 | 3061 3079 | 3211 3209 | |
| 17 | 130.50.3150 (50.3150) | 131.50.3150 132.50.3150 | 133.50.3150 134.50.3150 | 3432 | 2868 | 270 | 258 | 65 | 3104 | 3090 | 3213 | 3196 | 8 | 3342 | 2958 | 72 | Φ45 | 42 | 84 | 180 | 20 22 | 174 158 | 3536 3537.6 | 139 126 | 2768 2758.8 | 4551 | 5025 5009 | 4954 4988 | |

Note: Mounting Hole (n - Φ) may be replaced with Screw Hole (n-M). The length of Screw Hole: T. The type of product are as follows: Type 0 (Inner and Outer Ring: Φ), Type 1 (Inner and Outer Ring: M), Type 2 (Outer ring:M, Inner ring: φ), Type 3 (Outer ring: φ, Inner ring: M).

CHANGZHOU AOXUAN HEAVY BEARING CO.,LTD.

ADD:NO.158, Xinyuan 3RD Road, Xinbei District, Changzhou, Jiangsu, China

<https://aoxuanbearing.com>